

TRANSFORMING AIR PURIFICATION

**750+**  
wall mount



SEEKS, CAPTURES AND



**inactivates  
indoor  
pathogens.**

CHANGE IS IN THE AIR.

**Greentech 750+ wall mount**  
Active Air Purifier with PCO Technology

We measure success in microns.

**Applications:**

Workshops • Offices • Schools  
Day Care Facilities • Nursing Homes • Nail  
Salons • Veterinary Clinics • Motor Coaches  
Public Restrooms

- Active Air Purification
- No Ductwork Required
- Easily Mounts to Wall
- 24/7 Odor and Particulate Reduction
- Replaceable PCO Cell and MERV filter +

# Benefits of Greentech's 750+ Wall Mount



Continuous Purification



Reduces Odors



Mounts to Save Space



Sized for Multiple Locations



Wide List of Applications

## Active Oxidation Improves Air Quality



Providing continuous air purification, this permanently mounted unit is perfect for spaces without HVAC duct access. Greentech's 750+ Wall Mount features the same active air purification technology developed and used by NASA.



Photocatalytic oxidation (PCO) technology uses energy to activate a catalyst, turning moisture into products that continuously clean your space.



AOPs are propelled out into your space to hunt down particulates, even the very small ones. At the same time, negative ions go out and charge particles such as dust, pollen and pet dander, causing them to drop out of your breathing space.



With a reactive surface area more than 16x greater than the competition, Greentech's 750+ Wall Mount continuously purifies your space. The result is the reduction of allergens from pets, pollen, and smoke, as well as odors from mold, mildew, and more.

## Features and Specifications

### UNIT

- Models: Greentech SIREN 750+ Wall Mount 1X5789  
Greentech 750+ Wall Mount NO3 (no ozone) 1X5821
- Dimensions: 11.92" H x 9.72" W x 3.64" D
- Metric: 303mm H x 247mm W x 93mm D
- Weight: 3.3lbs (1.5kg)
- Materials: Powder Coated Aluminum
- Unit Warranty: 2 Year Manufacturer's Warranty

### PERFORMANCE

- Airflow: 70 CFM
- Optional Ozone Output: < 0.05 ppm
- Coverage: up to 750 ft<sup>2</sup>

### POWER

- Input Voltage: 24VDC
- Operating Voltage 24VDC
- Supply Power: 120-240VAC | 17W
- Operating Power: 24VDC | .67A

### TECHNOLOGIES

- PCO: Photocatalytic Oxidation
- Bipolar Ionization Module (BPI)
- Activated Oxygen (Ozone) - Optional

## To Use This Product Correctly

- 1 Read All Instructions Carefully in User Manual Before Operating Purifier.